ТЕЗИСЫ ДОКЛАДОВ

**МЕЖДУНАРОДНАЯ КОНФЕРЕНЦИЯ
«Перспективные материалы с иерархической структурой
для новых технологий и надежных конструкций»**

**X МЕЖДУНАРОДНАЯ КОНФЕРЕНЦИЯ
«Химия нефти и газа»**

Томск

Издательский Дом ТГУ

2018

DOI: 10.17223/9785946217408/325

SHEAROGRAPHIC NON-DESTRUCTIVE TESTING OF HONEYCOMB CFRP PANEL

^{1,2}Burkov M.V., ¹Lyubutin P.S., ¹Byakov A.V.

¹*Institute of strength physics and materials science SB RAS, Tomsk, Russia*

²*Tomsk Polytechnic University, Tomsk, Russia*

Carbon fiber reinforced polymers (CFRP) are increasingly applied in different industries. Structural and technological advantages provided by these materials determine their wide usage in newly designed aircrafts: Boeing 787 and Airbus 350XWB have about 50% wt. of composites in the structure. However composites have disadvantages: susceptibility to impact damaging due to viscoelastic deformation behavior. Thus impacts during aircraft operation lead to the formation of large amount of barely visible impact damages (BVID) which can grow over time producing cracked and delaminated defects. Any formed defects should be detected and repaired timely but the areas of CFRP skins are quite large demanding fast and productive non-destructive testing (NDT) to reduce maintenance time.

Traditional ultrasonic NDT method is applicable to testing of CFRP, but time consuming due to small scanning area. Due to non-contact and full-field application shearing speckle pattern interferometry (or shearography) is a robust NDT method which measures the strain of the testing object directly. Analysis of the strain fields and searching for non-homogeneities allow revealing damages and flaws in different structures. Finally shearography provide not only qualitative investigations (to identify and evaluate the defect) but also quantitative: measuring in-plane and out-of-plane strains with high accuracy.

The paper deals with application of newly designed shearographic device and developed software for digital processing of the shearograms. Based on the previous studies the robust algorithm for digital processing of speckle images was established. It is based on the sin/cos filtering with iterative approach providing smooth high contrast phase map without any disturbances and loss of phase information. The software for image capturing and processing procedures was developed. The device utilizes 5 Mpx CCD image sensor and five step phase shifting technique using piezodriven mirror in order to retrieve relative phase change. The lasers used are four DPSS 50 mW modules.

The tests were carried out on honeycomb panel (part of Sukhoi Superjet 100 rudder) with CFRP skins (lay-up of [(0,45,-45)₂, 0]). The experimental testing of the technique consists in detection of BVID of honeycomb panel obtained using drop-weight technique. There were 5 impacts with a step of 1 J. After each impact procedure the NDT testing was performed: the proposed device was applied along with thermal loading to visualize the defects.

The obtained shearograms easily revealed the BVIDs as a non-uniformities in the strain fields. The honeycomb specimens show the regular texture associated to the core while stacking of plies in the laminate is easily seen in the shape of straight lines coincidental to the direction of reinforcement. The results are analyzed and discussed in view of sensitivity of shearography to BVID and delamination.

Acknowledgements

This work was performed within the frame of the Fundamental Research Program of the State Academies of Sciences for 2013-2020, line of research III.23 and with a partial support of RF President Council Grant for the support of leading research schools NSh-5875.2018.8 and RF President grant SP-2167.2016.3.