

## CATALYSIS: FROM SCIENCE TO INDUSTRY

*Proceedings of  
V International scientific school-conference for young scientists*

September 25-29, 2018

Tomsk 2018

## Effect of Mo:V ratio on surface phase composition and catalytic characteristics of $V_2O_5$ - $MoO_3/Al_2O_3$ catalysts for oxidative dehydrogenation of propane

T.S. Kharlamova, K.L. Timofeev, O.V. Vodyankina

*Tomsk State University, Tomsk, Russia*

kvintkl@gmail.com

Supported vanadia composites are known as promising catalysts for oxidative dehydrogenation (ODH) of light alkanes including propane. A high catalytic performance of such catalysts is caused by the distribution of vanadium over the support surface in the form of 2D vanadia species. However, a low selectivity due to propylene overoxidation remains a challenge. Modification of vanadia catalysts with oxides of various metals (such as Mg, Mo, etc.) was shown to contribute to the increase of selectivity towards the target product.<sup>1-2</sup> At the same time, the optimal composition and structure of the active species in the multicomponent systems as well as their relationship with the catalytic properties remains unclear. In our previous work, the features of the formation of active species in the supported monolayer  $V_2O_5$ - $MoO_3/Al_2O_3$  catalysts for ODH of propane depending on the preparation approach were studied, with the consecutive impregnation of alumina support firstly with the solution of vanadium precursor and secondly with the solution of molybdenum precursor being the most advantageous. The present work is focused on the study of the effect of the active components ratio in the monolayer  $V_2O_5$ - $MoO_3/Al_2O_3$  catalysts on their catalytic properties towards propane ODH.

A series of  $V_2O_5$ - $MoO_3/Al_2O_3$  catalysts with a total V + Mo content corresponding to the monolayer surface coverage and different V : Mo ratio were prepared by the consecutive support impregnation of alumina support firstly with the solution of vanadium precursor and secondly with the solution of molybdenum precursor. Ammonium metavanadate  $NH_4VO_3$  and ammonium heptamolybdate  $(NH_4)_6Mo_7O_{24}$  were used as starting compounds of the supported components. To increase the solubility of  $NH_4VO_3$  and  $(NH_4)_6Mo_7O_{24}$ , oxalic and citric acids were used, respectively. The vanadium content in the  $V_2O_5$ - $MoO_3/Al_2O_3$  catalysts prepared was 0.15, 0.3, 0.5, and 1 monolayer. The intermediate  $V_2O_5/Al_2O_3$  and  $V_2O_5$ - $MoO_3/Al_2O_3$  target samples were calcined at 500 °C. A complex of methods including low-temperature nitrogen adsorption, UV-vis DR and Raman spectroscopy was used to study the textural characteristics, phase composition and structural characteristics of the obtained samples. The catalytic properties of the samples were studied in the reaction of oxidative dehydrogenation of propane.

According to UV-vis DR and Raman spectroscopy, the supported components are present in samples in the form of surface oligomeric or polymeric  $VO_x$  and  $MoO_x$  species, with V-O-Mo bonds being formed at the interfaces of the species. The effect of composition and structural features of the surface species formed in  $V_2O_5$ - $MoO_3/Al_2O_3$  catalysts on their catalytic properties are considered in details.

### References

1. Grant, J.T.; Venegas, J.M.; McDermott, W.P.; Hermans, I. *Chem. Rev.* **2018**, *118*, 2769 – 2815.
2. Liu X., Duan L., Yang W., Zhu X., *RSC Adv.* **2017**, *7*, 34131.