ТЕЗИСЫ ДОКЛАДОВ

INTERNATIONAL WORKSHOP

**«Multiscale Biomechanics and Tribology
of Inorganic and Organic Systems»**

МЕЖДУНАРОДНАЯ КОНФЕРЕНЦИЯ

**«Перспективные материалы с иерархической структурой
для новых технологий и надежных конструкций»**

**VIII ВСЕРОССИЙСКАЯ НАУЧНО-ПРАКТИЧЕСКАЯ
КОНФЕРЕНЦИЯ С МЕЖДУНАРОДНЫМ УЧАСТИЕМ,
ПОСВЯЩЕННАЯ 50-ЛЕТИЮ ОСНОВАНИЯ
ИНСТИТУТА ХИМИИ НЕФТИ**

«Добыча, подготовка, транспорт нефти и газа»

DOI: 10.17223/9785946218412/104

**EFFECT OF PRE-STRAIN ROLLING PATH ON ABNORMAL GRAIN GROWTH IN
FRICTION-STIR WELDED AL-MG-SI ALLOY**

¹Kalinenko A., ¹Vysotskiy I., ¹Malopheyev S., ¹Mironov S., ¹Kaibyshev R.

¹*Belgorod State University, Pobeda 85, Belgorod 308015, Russia*

The fine-grained microstructures evolved during friction stir welding of aluminum alloys often exhibit abnormal grain growth during post-weld heat treatment. To avoid this undesirable phenomenon, a pre-strain rolling approach has been employed in the present study. The proposed method was based on the idea that the pre-strain rolling would promote recrystallization instead of the abnormal grain growth during the subsequent heat treatment. To validate this concept, the produced welds were cold rolled in two different directions – either parallel or perpendicular to the weld path – prior to the standard T6 tempering.

In both cases, the pre-strain rolling was found to be effective for suppression of the abnormal grain growth. Moreover, the revealed effect was sensitive to the rolling path. Specifically, the pre-rolling along the weld line resulted in the finest final grain size in treated-treated welds. This observation was explained in the terms of relatively high Taylor factor as well as low orientation stability of the stir zone texture for this rolling path, which enhanced recrystallization behavior during subsequent annealing.

This study was financially supported by the Russian Science Foundation, grant No. 19-49-02001. The authors are grateful to the staff of the Joint Research Center, «Technology and Materials» Belgorod State National Research University for their assistance with the mechanical and structural characterizations.